



Hallmark of Excellence



Making impossible things possible through constant innovation.

Vista Chemtech Pvt Ltd, is a flagship company of 'A SURANA GROUP', which are serving industrial segment since 1979. This ISO 9001 certified company has carved a niche for itself with its high quality and guaranteed products at competitive price.

Vista Chemtech Pvt Ltd, is a flagship company of 'A SURANA GROUP', which are serving industrial segment since 1979. This ISO 9001 certified company has carved a niche for itself with its high quality and guaranteed products at competitive price.

The management of "A Surana Group" lies in the competent hand of dynamic entrepreneur Mr. Ashok Surana son of Late Chhotulal Surana of Sujangarh, Rajasthan. He has groomed the group to reach in a new horizon with his vast 34 years business experience.

Vista Chemtech Pvt Ltd is in continuous process of new innovation consistently along with building alliance to reach the hallmark of excellence. Vista Chemtech Pvt Ltd is engaged in the research and development of innovative cement additive and construction chemicals on a continuous process. As a result we are able to introduce time to time many innovative products.

Our products are being tested and used by leading cement manufacturer in India and abroad. We are confident that with our development team and network we shall be one

of the leading construction chemical manufacturers in near future.

We have an excellent team of highly qualified research people and new generation cement & concrete testing laboratory for any type of research and development work. So if you have any problem or development issue you can trust on us.

Our strength lies in the understanding of what technology works best with specific applications to solve the customer's problem. Our focus is on our customer's application and construction solution thus allowing the flexibility to offer the latest technology.

We also prepare 'Tailor made' product especially for you as per your need. We provide guaranteed quality products at competitive price. We also provide Lab trial and plant trial on performance.




We develop solutions that make future-orientation, quality construction durability and optimize customers' processes in lower costs. We make impossible things possible with our innovative products and services.



WATERPROOFING

	PRODUCTS	DESCRIPTION	USES	DOSAGE/COVERAGE
	VISTA - IWA [Integral Cement Waterproofing Admixture]	Integral Cement Waterproofing liquid admixture for heavy duty damp proofing for concrete, mortars conforms to IS: 2645-2003 and IS:9103 - 1999	Admixture for concrete / mortar for waterproofing	100 gms per 50 kg bag of cement
	VISTA NO 1 [Integral Waterproofing Compound for mortar and concrete]	Normal setting waterproof semi paste additive for concrete and mortar conforms to IS: 2645-2003.	To reduce permeability of concrete and mortar for use in basement,	1 to 1.5 kg per 50 kg bag of cement
	VISTA NO 2 [Rapid / Quick setting / Hardening Compound for mortar and concrete]	Extra fast set waterproofing plugging compound in liquid form	Excellent time tested liquid admixture for emergency / immediate repair work and Instant leak plugging and quick fixing of nozzle.	37% by weight of cement. Setting time 30 to 60 secs.
	VISTA NO 3 [Quick setting Compound for cement mortar and concrete]	Multipurpose cement mortar & concrete additive in liquid form for quick setting or rapid hardening of the same	Rapid hardening for Tunnel, Basement and any repair work. Highly useful for stoppage of water ingress through underground structure.	1 part of material with 3 to 4 part cement
	VISTA CERACOAT [Waterproof and Insulation coating for building materials]	An emulsion of high grade ceramic polymer, contains ceramic particles which are heat and cold dissipating elements.	Used to provide coating to insulate most building materials from solar heat. It does not require a primer due to unique properties of material	4.0 sqm per liter in one coat.

PROTECTION & REPAIR

	PRODUCTS	DESCRIPTION	USES	DOSAGE/COVERAGE
	VISTA SUPER LATEX-SBR [All purpose waterproofing and bonding compounds]	Synthetic latex emulsion based on modified Styrene Butadiene Rubber (SBR) which can be added to any cementations formulation	It has wide range of uses for waterproofing, as a grout admixture cement slurry, additive to repair mortars & renderings, putties and in either forms in the repair and rehabilitation	250 to 500 gms per sqm coating
	VISTA SUPERCRETE [Acrylic Polymer based coating for waterproofing and repairing compound]	Acrylic polymer based Cementitious coating and repairing compounds when used with cement and fine sand to form an impermeable coating by blocking the capillaries and pores of the substrate of concrete. It is also UV resistant	for use in structures that required to be protected against the ingress of moisture, like Roof / Terrace, Basements, water tanks, swimming pools, retaining walls, Bridge walls, Tunnels, Sewage tanks, Dams, Reservoirs, Dock gates etc.	700 gms per sqm in two coat
	VISTA RUST STOP [Anti Corrosive Coating]	It is a modified acrylic polymer based cementitious, anticorrosive protective coating	Prevent corrosion for all types of reinforcement / damaged steel structure	600 to 750 gms per sqm



PROTECTION & REPAIR

	PRODUCTS	DESCRIPTION	USES	DOSAGE/COVERAGE
	VISTA RUST REMOVER [Rust Removing Agent]	It is a rust removing agent for steel reinforcement and steel surface	Used for removing rust from corroded steel, cleaning of new/old steel reinforcement	4 to 6 sqm per kg in two coats
	VISTA FLOOR TOP - M [Metallic surface hardening compound]	Graded metallic granules formulation with cement to form extra tough concrete floors	Foot path, godown and ware houses where metal wheeled carts ply, runway, heavy traffic lanes, service station, parking lots, skating rinks, playing courts, garages and workshops, foundries, steel casting units, etc.	2 to 3 kg per sqm for light duty floor and 5 to 7 kg per sqm for heavy duty floor
	VISTA FLOOR TOP - NM [Non-metallic surface hardening compound]	Factory processed and specially graded hardwearing aggregates which have been selected for abrasion and wear resistant properties as well as shape and size	It is recommended for workshop, warehouse, machine shops, ramps, and car parks that are subjected to heavy traffic	In 2:1 ratio with cement - 3 kg per sqm for moderate duty, 5 kg per sqm for medium duty and 7 kg per sqm for heavy duty
	VISTA CRACKFIL PASTE [Highly flexible filler for internal & external surface cracks]	Highly flexible single component crack filler ideally suitable for internal & external surface cracks	Suitable for repairing cracks in plaster. Useful for sealing cracks in ceiling and the junction of brickwork & columns or beams	1 kg seals 100 Rft of 5mm wide cracks
	VISTA POXYBOND 2115 /2118 /21120 [High strength epoxy repair mortar]	Three component solvent free, fast curing high strength epoxy resin mortar	It is filled into concrete voids/pockets for carrying out structural repairs	Depending upon the required thickness
	VISTA DAMPCOAT [Multipurpose damp proof coating compound]	Two component water thinable epoxy compound	Internal coating to arrest seepage and dampness of water tanks, inner walls, ceilings, underground car parking etc.	Comp.A:Comp.B:Water = 1:1:1. mix slowly until a brushable consistency. 1st coat - 6 to 8 sqm/kg, 2nd coat - 8 to 10 sqm/kg

GROUT & EPOXY GROUT

	PRODUCTS	DESCRIPTION	USES	DOSAGE/COVERAGE
	VISTA GROUT GP [Non shrink cementitious grout]	High Strength, free Flowing Non-Shrink, Non-metallic and Chloride Free Grout conforming to BS-1881, Part 116-1983	used for grouting of bolt pockets and base plates grouting of all equipments, Columns in pre-cast construction concrete, Grinders, Beams, Repair & Rehabilitation of Structures	1.9 to 2 kg powder with 1 litre water at flowable consistency
	VISTA GROUT HS [High strength Non shrink cementitious grout]	Ultra High Strength, free Flowing Non-Shrink, and Chloride Free Grout conforming to BS-1881, Part 116-1983	Special grouting applications where early strength development is the main criteria.	2 to 2.25 kg powder with 1 litre water at pourable consistency
	VISTA NSPG [Non shrink plasticised expanding grout admixture]	Plasticized Admixture for cementitious pressure injection grouting in concrete	Grouting of voids, tunnels and shaft lining, underpinning below foundation, underground structure	250 gms per 50 kg bag of cement
	VISTA POXYBOND - 21 [High strength injectable epoxy grouting compound]	Designed especially for pressure injection grout into concrete for carrying structural repairs. Due to its low viscosity it can be injected into extremely fine cracks also	Used to fill and seal voids cracks in structure such as bridge and other civil-engineering building, industrial and residual building such as column, beam, foundation, walls, floor and water retaining structures	Comp.A - 2 Comp.B - 1 Depending upon the gap size
	VISTA POXYBOND - 215 [High strength self leveling injectable epoxy grouting compound]	Three Component solvent free, free flowing, non-shrinking fast curing epoxy resin system used for pour able epoxy grout	Cracks and voids of any nature can be successfully sealed	Comp.A - 2 Comp.B - 1 Comp.C - 5 Depending upon the gap size




GROUT & EPOXY GROUT

	PRODUCTS	DESCRIPTION	USES	DOSAGE/COVERAGE
	VISTA PU GROUT [Single component Polyurethane injection grout]	It is mainly developed as versatile non-ionic sealant in concrete structure	Used for injection into cracks in concrete to stop the flow of moving water	Depends on the quantity at leakages from the structures

CONCRETING AIDS

	PRODUCTS	DESCRIPTION	USES	DOSAGE/COVERAGE
	VISTA SHUTTERING OIL MRA-OB [Oil based mould release agent]	Low viscous mineral oil based shutter release agent. Ready for direct application and use	"provide quick, clean and easy stripping of moulds or frame work; obtain clean and smooth concrete surface; protect steel and wooden frame work"	30 to 60 Sqm per Ltr
	VISTA SHUTTERING OIL MRA-WT [Water thinnable based mould release agent]	Concentrated and emulsified chemical shutter release agent	Easy stain free release of concrete mould and frame of all types particularly where wooden formwork is used and demoulding or stripping times exceed 24 hours.	1 Ltr when diluted with 5-6 Ltr water will cover - 30 to 60 sqm/ltr (wood) 40 to 60 sqm/ltr (steel or plastic)
	VISTA CURING COMPOUND - AP [Resin based aluminium pigmented concrete curing compound]	Concrete curing compound to prevent premature water loss from concrete. It is based on synthetic film forming resin and leafing grade micro fine Aluminum pigment	Benefit for large area concrete surface, highway-Road construction, Airport Runways and Bridge works, Pre stressed beam and piers, Exposed Surface of Dams, Slopping and angular surface where pond curing is not possible	3 to 5 sqm per ltr, but depends on site condition
	VISTA CURING COMPOUND - WB [Wax based concrete curing compound]	Based on Low viscosity emulsion pigmented with titanium-di-oxide for reflection of sunlight to dissipate surface heat	Very useful for large area concrete surface, highway-Road construction, Airport Runways, Apron and hard standing, Pre stressed beam and pillars, Exposed Surface of Dams, Retaining walls, Canal Lining	5 to 6 sqm per ltr but depends on site condition
	VISTA BOND EP [Solvent free epoxy resin bonding compound]	Supplied as a two part material in pre weighed quantities for ready onsite mixing and use	For bonding new cementitious materials to existing cementitious surfaces. For use on horizontal surfaces and on vertical surfaces where mortar or concrete can be supported by formwork	Approximately 2.6 sqm/kg. Actual coverage will depend upon the texture and porosity of the substrate being covered
	VISTA WALL PUTTY [Water resistance white cement based wall putty]	White cement based waterproof plaster for interior and exterior application	It protects as well as decorates cement plaster and concrete structures both interior and exterior.	Approximately 1 kg powder is adequate to cover 2 to 2.5 sqm in 1mm thickness.

TILE ADHESIVE & GROUT

	PRODUCTS	DESCRIPTION	USES	DOSAGE/COVERAGE
	VISTA TILE FIX [Single component polymer modified tile adhesive in powder form]	High quality ready mix cement based tile adhesive, conforming to IS: 15477-2004	For the permanent fixing of ceramic and mosaic tiles on wall, floor, wet areas like kitchen and Bathrooms	Approx. 4 kg per sqm @ 2mm thickness
	VISTA TILE FIXER [Single component polymer modified tile adhesive in paste form]	High concentrate waterproof polymer based strong tile fixer	For fixing of tile on floor, walls, stairs bathrooms, kitchen, laboratories, hotels, shopping malls, swimming pool etc.	Approx. 3-4 kg per sqm @ 3mm thickness. Mixing ratio 1:100:40 of Fixer : Cement : Water
	VISTA TILE GROUT [Pigmented cementitious tiles joint filler]	Blend of specially selected cements, fillers and synthetic organic polymers for ready to use	As a grout for tile joints for kitchen, bathroom, swimming pool	300 ml water is required for 1 kg material to form thick paste.



UAN : WB08A0003595

ESTEEMED CLIENTS - having trust on us



VISTA CHEMTECH PVT. LTD.
[AN ISO 9001 CERTIFIED CO.]

Corporate Office :

A Surana Group of Industries

'VISTA', 6C, Elgin Road, Kolkata - 700020

T : +91 33 4004 5841 / 2236 0469 / 2215 5513

F : +91 33 2237 9394

E : vista@asuranagroup.com

W : www.asuranagroup.com

Works :

• Ankleshwar :

GIDC, PANOLI, Ankleshwar,

Dist. - Bharuch - 394116, Gujarat

• Howrah :

Ranihati-Amta Road, Amta Howrah - 711322

• Kolkata :

'VISTA HOUSE' 7/1B, Grant Lane, Kolkata - 700012

Show Room & Office :

- OT Road, Post - Balasore, Dist. - Balasore - 756001, Odisha
- 8, Ashapura Nagar, Pal Gaon, Jodhpur - 342008, Rajasthan
- New Colony, Tilmapur, Ashapur, Varanasi - 221007, U. P.

Registered Office :

76, Khengra Patty Street, Kolkata - 700007

Other Group Companies :

Arihant Nexzen Marketing Pvt. Ltd.

Dr. Vista Natural Products (India) Pvt. Ltd.



Toll Free No.: 1800 121 5440