



VISTA

VISTA SUPER LATEX(SBR)

ALL PURPOSE WATERPROOFING AND BONDING COMPOUND

DESCRIPTION :

Vista Super Latex is a Single Component synthetic latex emulsion based on modified Styrene Butadiene Rubber (SBR) which can be added to any cementations formulation, to achieve bonding and waterproofing properties.

USES :

Vista Super Latex has wide range of uses for waterproofing, as a grout admixture cement slurry, mortar using it as an additive to repair mortars and renderings, putties and in either forms in the repair and rehabilitation industry, rendering and tile fixing etc and bonding old concrete to new concrete.

ADVANTAGES :

- Easy to use
- Excellent adhesion to a wide range of substrates.
- Improves flexibility of the treated area.
- Improve tensile and flexural properties.
- Improves chemical resistance to substrates.
- Drastically reduces permeability.
- Improves workability and adhesion of mortars.
- Strength remains unaffected.
- Can be diluted with water to suit specific needs.
- Prevents finished surfaces from cracking.
- Improves bond to mother substrates.
- Weatherproofs walls from rising dampness / salt petre action.

APPLICATION :

Surface Preparation: The substrate must be structurally sound, clear and dust free, oil, grease and contaminants must be removed mechanically. Smooth surface must be scrubbed. Surface should be damped with water prior to application of the bonding primer, modified mortar or concrete. All excess water should be removed from the surface.

PROPERTIES :

Aspect	Milky White Liquid
pH	7 - 9
Specific Gravity	1.02±0.01
Compressive Strength (Min) at 28 Days	250 kg/ cm ²
Bond Strength (Min)	30kg/ cm ²
Flexural Strength (Min) at 28 Days	70kg/ cm ²



VISTA

Application & Recommended Consumption:

Ingredients	Bonding Coat	In Mortar / Render	In Concrete
Vista Super Latex	1 part by weight	1 part by weight	1 part by weight
Cement	2 Parts by weight	10 part by weight	10 part by weight
River Sand	Nil	4 part by weight	5 part by weight
10 mm nominal size Coarse Aggregates	Nil	Nil	30 part by weight
Water	1 to 4 part	2 to 10 part by weight	2 to 4 part by weight

OTHER APPLICATIONS :

Mix Proportion	As a Putty for joints	Sealant for tile joint
Vista Super Latex	1	1
Water	1	2
Cement (Grey)	4	
River Sand	12	
White Cement		4
Lime stone Powder		12
Colour Pigment		As required

SHELF LIFE :

12 months from the date of manufacturer in unopened conditions. To be stored in cool and dry place away from direct sunlight.

PACKING :

500 gm, 1kg ,5kg and 50kg Containers.

NOTE :

- The contents of the technical data sheet are for general information and guideline only. Results shown here are generated from our laboratory or from our site experiences. This behavior may change as per prevailing condition at the time of application.
- VISTA maintains a team of technical trained professional to provide full support in regards to any of our products.

Manufactured by

VISTA CHEMTECH PVT. LTD.

(An ISO 9001 Certified Co.)

A SURANA GROUP OF INDUSTRIES

Corporate Office :

7/1B, Grant Lane, Kolkata – 700 012, (INDIA)

T : +91 33 2237 9394 / 2236 0469 / 2215 5513

F : +91 33 2237 9394

Works :

PO - Jalabishwanathpur, Amta

Howrah - 711 322

E : vista@asuranagroup.com ; W : www.asuranagroup.com ; S : asuranagroup

Ankleshwar • Balasore • Gangtok • Howrah • Kolkata