



VISTA

VISTA TILE GROUT

PIGMENTED CEMENTITOUS TILES JOINT FILLER

DESCRIPTION :

Vista tile Grout is a blend of specially selected cements, fillers and synthetic organic polymers. When added to water it readily blends to produce a smooth creamy paste which when set is water and mould resistant. Vista tile Grout is used in conjunction with Vista tile adhesives.

USES :

As a grout tile joints in:

- Kitchens
- Bathrooms
- Shower Stalls
- Swimming pools

ADVANTAGES :

- Low cost service life – Mould resistant, tropical grade
- Easy to apply – Just add water for a thixotropic, non slump grout
- Can be used in submerged conditions

APPLICATION :

Apply Vista tile Grout to the spaces between tiles using a sponge or a small piece of soft cloth. Work the mixture into the joints and around the edges. Remove surplus material from the face of the tiles with a dry cloth and run the tip of a gloved finger or a suitable rounded tool along the grout to level it off and form of profile.

When the grout is dry, clean the tiles with a damp sponge to remove any excess material. It is advisable to remove uncured grout from textured tiles prior to setting, failure to do so may result in difficulty in removal.

PROPERTIES :

Specific gravity	1.9 to 2.0 g/cc
Working time at 20°C	90 minutes
Working time at 30°C	30 minutes
Compressive Strength @ 28 Days (ASTM C 109)	38 N/mm ²
Tensile strength @ 28 days(BS 6319; Pt 7)	3 N/mm ²

PREPARATION:

All tiles must be securely fixed in place and thoroughly cleaned before Vista tile Grout is applied. The gap between tiles should not exceed 4mm. tiles joint filling should only be done 24 hours after fixing the tiles

MIXING:

300 ml of water is required for each kg bag of Vista tile Grout. Add powder to water and mix until a uniform, lump-free, thick creamy paste is produced, allow to stand for ten minutes prior to use.



VISTA

CLEANING:

Vista tile Grout should be removed from tools, equipment and mixers with clean water immediately after use. Cured material can only be removed mechanically.

LIMITATIONS:

Vista tile Grout should not be used when the temperature is below 5 °C and falling. The product should not be exposed to moving water during application. If any doubts arise concerning temperature or substrate conditions. Consult your local Vista Office.

SHELF LIFE:

Vista tile Grout has a shelf life of 12 months if kept in a dry store in the original, unopened bags or packs

STORAGE CONDITIONS:

Store in dry conditions in the original, unopened bags or packs. If stored at high temperature and / or high humidity conditions the shelf life may be reduced.

Packing:

Vista Tile Grout is supplied in 1kg HDPE packet.

PRECAUTION:

Health & Safety Instruction: VISTA TILE GROUT is non-toxic. Any splashes on the skin should be washed immediately with water and medical advice sought.

Fire: VISTA TILE GROUT is non-flammable

NOTE :

- The content of the technical data sheet are for general information and guideline only. Results shown here are generated from our laboratory or from our site experiences. This behavior may change as per prevailing condition at the time of application.
- VISTA maintains a team of technical trained professional to provide full support in regards to any of our products.

Manufactured & marketed by

VISTA CHEMTECH PVT. LTD.

(An ISO 9001 Certified Co.)

A SURANA GROUP OF INDUSTRIES

Corporate Office :

7/1B, Grant Lane, Kolkata – 700 012, (INDIA)

T : +91 33 2237 9394 / 2236 0469 / 2215 5513

F : +91 33 2237 9394

Works :

PO - Jalabishwanathpur, Amta

Howrah - 711 322

E : vista@asuranagroup.com ; **W :** www.asuranagroup.com ; **S :** asuranagroup

Ankleshwar • Balasore • Gangtok • Howrah • Kolkata